

# 4

### **Aquifer Exemption Boundary**

#### Objective:

- Demonstrate that no existing domestic well that is currently used for human consumption is using water from the AE Area
- Demonstrate that no existing domestic well could produce water from the AE Area for the entire mine life
- Approach: Use accepted EPA capture zone methods and site data to delineate capture zones

### Capture Zone Time Frame

- We will perform calculations of capture for the 8 year mine life provided in the issued permit.
- This is consistent with:
  - 40 CFR 146.6
  - Region 6 EPA's response to UEC's Application received on May 27, 2011




#### Capture Zone Approach

- 1. Tabulate the rural domestic wells to be considered in the AOR and detail what strata each is completed in, where known.
- 2. Calculate average hydraulic gradients in each stratum
- Calculate the 8 year capture zones for each rural domestic well and plot relative to the AE Boundary



### 8 year Capture Zone



# •

#### Variables / Nomenclature

```
Q = Extraction rate at rural/domestic well (L3/T)
K = Average hydraulic conductivity of stratum (L/T)
      Average thickness of stratum (L)
b =
      Average transmissivity (K * b) of stratum
(L2/T)
i =
      Average hydraulic gradient (L/L)
      Porosity of stratum (L3/L3)
Ф=
      Average seepage velocity (L/T)
V =
      Coordinate parallel to seepage velocity direction
X =
      Coordinate normal to seepage velocity direction
y =
```

## Capture Model Properties

		Average Hydraulic Gradient	
Stratum	Average Thickness (ft)	Magnitude (ft/ft)	Direction (degrees)
Α	65	TBD	TBD
В	36	TBD	TBD
С	36	TBD	TBD
D	80	TBD	TBD

 We have good sand hydraulic properties from two large-scale pump tests and a calibrated flow model of the B-sand

#### Rural/Domestic Use


- 2009 Water use survey data (Kevin Kluge, TWDB)
- Based upon municipal use and population TWDB does not calculate a county gpd/capita for rural/domestic
- Goliad County = 119 gpd/person
  - State average = 150 gpd/person
- Average household in Goliad County is comprised of 2.6 people
  - http://www.goliadcc.org/index.php/re-location-info.html

### Rural/Domestic Use

- 2.6 people x 119 gpd/person = 309.4 gpd
- $\blacksquare$  309.4 gpd = 0.215 gpm = 41.4 ft3/day


# •

## Calculation of the 8 year Capture Zone




# 4

## Conservative Aspect of the Calculation



Y max = +/-Q/2TISteady-state Xo = - Q / 2  $\pi$  T I Steady-state

# Travel Time Calculation from X<sub>1</sub> to X<sub>2</sub>



Travel Time from  $x_2$  to  $x_1 =$ 

$$\{vx_2 - Q/2\pi b\phi [ln (vx_2 + Q/2\pi b\phi)] / v^2 - \{vx_1 - Q/2\pi b\phi [ln (vx_1 + Q/2\pi b\phi)] / v^2 \}$$

# Product to EPA

- Review all wells in the AOR and provide verification of where the wells are completed where we have data
- Develop reasonable estimates of:
  - Aquifer properties
  - Hydraulic gradients
  - Rural/domestic pumping rate



- Provide plots of the 8 year capture zones for each rural/domestic well in the AOR
  - If a well is known to be completed in a particular stratum, calculations for that well will be limited to that stratum
  - If completion of a well is unknown, the calculations will be performed assuming all four potential strata
- Technical memorandum documenting results

